MODEL XL-85s DIAGRAM PRIMARY CABINET DIMENSIONS

SPECIFICATIONS (CENTIMETERS ARE RESPRESENTED BY [])

MAX TV SIZE: 86"

MAX WEIGHT CAPACITY: 175 LBS [79.4 KG] MAX TRAVEL [EXTENSION] : 65" [165.1]

LIFT SYSTEM HEIGHT: 40.75" [103.5] TO 55.5" [141]

MAX TV HEIGHT : 49" [124.5] MANUAL SWIVEL RANGE: +/- 180°

QUICK REFERENCE DIMENSION GUIDE (USE WHICHEVER IS GREATER)


TV DIMENSIONS : W_____, H_____, D____

MIN. INTERIOR CABINET WIDTH W + 2'' [5.1] = _____ OR 32.5'' [82.6]

MIN. INTERIOR CABINET HEIGHT: SEE CHART ON PAGE 2

MIN. INTERIOR CABINET DEPTH : D + 8.5" [21.6] = _____

MIN. LID CUTOUT WIDTH = TV WIDTH + 2" [5.1] OR 32.5" [82.6] WHICHEVER IS GREATER



MIN. LID CUTOUT WIDTH = TV WIDTH + 2" [5.1] OR 32.5" [82.6]

WHICHEVER IS GREATER

NOTES:

- 1. THE CABINET BOX SHOWN IN THE DIAGRAM IS FOR REFERENCE ONLY AND IS NOT PROVIDED WITH THE LIFT SYSTEM
- 2. LIFT MECHANISM IS POWDER COATED BLACK STEEL. COLORS IN DIAGRAM ARE FOR CLARITY ONLY
- 3. LIFT WILL NOT OPERATE WHEN SWIVELED OUTSIDE OF HOME POSITION
- 4. LIFT ENCLOSURE'S REAR PANEL SHOULD BE CONSTRUCTED TO WITHSTAND A HORIZONTAL LOAD OF 600 LBS [272.2 kg] OR MORE

MIN. LID CUTOUT DEPTH = TV DEPTH + 8.5" [21.6]




MIN. INTERIOR CABINET DEPTH = TV DEPTH + 8.5" [21.6]




COPYRIGHT 2021 - ALL RIGHTS RESERVED UPDATED 3/24/21

MODEL XL-85s DIAGRAM PRIMARY CABINET DIMENSIONS - CONTINUED



MIN. REQUIRED TRAVEL before TV can be swiveled (SEE NOTE 1)

MINIMUM REQUIRED TRAVEL TABLE		
TV HEIGHT	MINIMUM REQUIRED TRAVEL before TV can be swiveled	
32" [81.3]	57.25" [145.5]	
33'' [83.8]	59.75" [151.8]	
34'' [86.4]	62.25" [158.1]	
35" TO 49" [88.9 TO 124.5]	MAX TRAVEL REQUIRED	



FOR INTERIOR CABINET HEIGHT **SEE CHART**

INTERIOR CABINET HEIGHT TABLE		
TV HEIGHT	MIN INTERIOR CABINET HEIGHT	MAX INTERIOR CABINET HEIGHT
32" [81.3]	40.75" [103.5]	52.5" [133.4]
33" [83.8]		53.5" [135.9]
34'' [86.4]		54.5" [138.4]
35" TO 49" [88.9 TO 124.5]	TV HEIGHT + 6" [15.3]	55.5" [141]


FOR TV HEIGHT, ALWAYS USE MANUFACTURER SUPPLIED "TV WITHOUT STAND" HEIGHT

IMPORTANT NOTES:

- 1. MINIMUM REQUIRED TRAVEL = THE AMOUNT OF EXTENSION REQUIRED IN ORDER TO SWIVEL THE TV AND CLEAR THE CENTER RISER; USE CHART
- 2. MAXIMUM TV TO SURFACE GAP = 63.125" [160.3] MINUS "TV HEIGHT" MINUS "LID THICKNESS"
- 3. CENTER RISER WILL BE EXPOSED REGARDLESS OF CABINET SIZE AND TV TO SURFACE GAP
- 4. MAX TRAVEL FOR THIS SYSTEM IS 65" [165.1]



MODEL XL-85s DIAGRAM CABINET REFERENCE DIMENSIONS



NOTES:

- 1. LID SUPPORTS ALLOW LID PLATE TO BE ADJUSTED FLUSH WITH UNDERSIDE OF LID
- 2. LID ATTACHMENT PINS ALLOW LID TO FLOAT WITH THE USE OF LID CATCHES
- 3. MINIMUM SEAM CAN BE REDUCED TO 0.0625" [0.2] WITH A 45 DEGREE BEVEL ON THE EDGES OF THE LID

