

HDMI 2.0A 4K60 18Gbps 1x2 & 1x4 Splitters

Features

- ◆ Supports HDMI 2.0A Deep Color & 3D / DVI 1.0 compliant
- ◆ HDCP 1.4/2.2 compliant
- ◆ Wide frequency range: 25MHz~600MHz
- ◆ Video bandwidth: 18Gbps
- ◆ Resolution up to 4K2K @ 60Hz
- ◆ Auto EDID Management
- ◆ EDID Emulation & Customizable EDID
- ◆ Supports xvYCC, x.v.Color & Deep Color
- ◆ Mini-USB port for firmware updating & EDID setup
- ◆ Supports Dolby Digital, DTS-HD and Dolby TrueHD audio
- ◆ HDMI & Power Connectors on same side for easy installation
- ◆ Ultra-low profile to fit behind displays



The DXE-122A 1x2 HDMI and DXE-142A HDMI 2.0A 4K Splitters with Auto EDID Management provides one of the most advanced HDMI splitter solutions by which the Ultra High Definition video and high quality audio can be transmitted to multiple locations without losing quality. The DXE-122A and DXE-142A support all 3D formats and true 4K2K video. EDID management can be one of the most important capabilities to a splitter. Taking it one step further Aurora has added the ability to customize EDID for complete EDID emulation. This allows full control over the source and what it will be allowed to do.

The DXE splitters have firmware upgrade capability via the USB port ensures compatibility now and in the future. With 48bit deep color video and high definition audio support, the DXE-122A and DXE-142A are suitable for high quality HDMI broadcasting, conference room, digital signage and education applications.

Technical Specifications

Model Name	DXE-122A/DXE-142A	
Technical		
HDMI/DVI compliance	HDMI 2.0A Deep Color, full 3D & 4K2K/ DVI 1.0	
HDCP compliance	HDCP 1.4/2.2	
Video bandwidth	Single-link 600MHz [18Gbps]	
Video support	Up to 4K2K @60	
HDMI Output Distance	720p 12bit up to 20m, 1080i 12bit up to 20m, 1080p 12bit up to 15m, 4K up to 7.5m (Note: Cable quality may impact distance)	
Audio support	DTS-HD Master Audio, Dolby TrueHD Dolby Digital, DTS, DVD-Audio, LPCM, SACD, MPCM	
Firmware update	Mini-USB port	
Input	1x HDMI	
Output	2x HDMI (DXE-122A)/ 4x HDMI (DXE-142A)	
EDID	Auto Management	
Mechanical		
Housing	Metal enclosure	
Dimensions [L x W x H]	DXE-122A	100 x 70 x 11mm (3.94"x2.76"x0.433")
	DXE-142A	150 x 70 x 11mm (5.91"x2.76"x0.433")
Weight	DXE-122A	0.08kg (2.82oz)
	DXE-142A	0.12kg (4.23oz)
Mounting	Attachable ears	
Power supply	5V 1A DC	
Power consumption	3.6 Watts [max]	
Operation temperature	0~55°C	
Storage temperature	-20~60°C [-4~140°F]	
Relative humidity	10~90% RH [no condensation]	

Note: Specifications subject to change without notice.

Important: Read User Guide for full specification.