

smart series

MODEL DRM95 30AMP

HUGE!
76,000 AMP
MAXIMUM SPIKE
2320 JOULES

OUT OF SIGHT - OUT OF MIND

Imagine having perfect sound
and vision... Now you can

High capacity premium series (dinrail
mountable) dynamic active tracking AC mains
filter + surge protection isolation module.

1 DYNAMIC ACTIVE TRACKING DOUBLE FILTRATION

32 SEPARATE PROTECTION & FILTRATION COMPONENTS

2 INTERNAL BACK EMF PROTECTED

3 HIGH TEMP / HIGH IMPACT POLYCARBONATE HOUSING

4 EMI/RFI NOISE REDUCTION FILTER TYPE

5 ALSO AVAILABLE 20AMP



Dimensions: 105 mm (W) x 96 mm (H) x 60 mm (D)

SPECIFICATIONS:

• Supply Voltage	240 VAC 50 Hz
• Maximum Current Rating	30 Amps 7200 W (VA)
• Clamping Voltage	275 VAC
• Reaction Time	Less than 1 Nano Sec
• Maximum Transient Spike Impulse Current (Amps)	76,000 Amps
• Maximum Energy Dissipation (Joules)	2320 Joules
• Protection Modes (all 3 conductors)	Active/Neutral Active/Earth Neutral/Earth
• Earth Leakage Range	Less than 1 mAmp
• Operating Conditions	Indoor/AC Mains
• Operating Temperature	-10 °C/+60 °C



www.thortechnologies.com.au